

AHI Supply, LP
PO Box 2789
Alvin, Texas 77512
Tel 281-331-0088 Fax 281-331-9813
www.ahi-supply.com



Stucco Products Division

To: _____ **Date:** _____

Attention:

From:

Subject: Submittal for approval

Project:

EPS Mastic

Product information:

EPS Mastic is a ready-mixed, ready to use acrylic based copolymer adhesive. This product is also used as an adhesive for wood-based sheathing.

Features:

- Water-based
- Interior or exterior
- Neutral White
- Notched Trowel Application

General information:

Spectrum EPS Mastic is intended to be applied to adhere foam profiles, embedded with fiberglass mesh over conventional stucco. This product is not to be used with EIFS or any exterior insulated finish system. (See additional EIFS warning below). This product may also be used to repair aged or damaged surfaces of masonry, brick, CMU, concrete or as preparation for the application of a decorative coating approved substrates.

EPS Mastic should be used as an adhesive only. Please note, do not use as a base coat, on pressure treated lumber or fire retardant surfaces. Thoroughly mix EPS Mastic to a smooth, homogeneous consistency before application.

Clean area and remove all dust, grease, oil, paint, dirt, efflorescence and any unsound concrete. Spectrum tintable primer must be applied over all cementitious products once they have been allowed to cure. Primer must be applied with a spray application and then back rolled with a paint roller. With a pH pencil, check the surface pH levels 4-6 hours after primer has dried. Dry time will depend on the surface temperatures, humidity, and porosity of material being coated. Randomly check the entire surface to ensure pH levels are below 10. Do not use on damp surfaces or on substrates with high moisture content.

Please note that you should not apply EPS Mastic when the temperature outside is lower than 40°F or when frost is predicted. Do not use in wet areas and protect work from rain for at least 24 hours.

Coverage on textures:

All coverage's are approximate, dependent on substrate and individual application techniques.
350 sq. ft. - 385 sq. ft.

DO NOT USE THIS PRODUCT AS A COMPONENT OF AN EXTERIOR INSULATION FINISH SYSTEM (EIFS) OR AS PART OF ANY EXTERIOR INSULATION FINISH APPLICATION REPRESENTED TO BE A SIMILAR GROUP COMPONENT BASED SYSTEM.

EIFS refers to an exterior insulation system in which the specific components are designed, formulated, tested and may also be certified by "EIMA", "ICBO" or other organization to ensure that the individual components are compatible with one and another and will successfully function together. All AHI products are sold independently and separately and have not been tested, designed, formulated, manufactured or certified by any entity to work together successfully in Exterior Insulation Finish Systems or as a part of any exterior insulation application represented to be similar group component based system.

WARRANTY: All Spectrum stucco coatings come with a limited 5 year warranty.

Thank you for the opportunity of furnishing this quality product on your important project!