

SPECTRUM BONDING AGENT and ACRYLIC ADMIXTURE

Benefits/Features

- Reduces cracks in stucco, mortar, plaster, grout and concrete.
- Improves bonding, impact and flexural strengths of stucco, mortar, plaster, grout and concrete.
- Water-based product cleans up with water.
- V.O.C. Compliant.

Coverage as Bonding Agent

200-300 square feet per gallon

Dilution Rates

As Bonding Agent use full strength.

As Admixture dilute from 1 part Bonding Agent to 1 part water, up to 1 part Bonding Agent and 8 parts water as desired.

Precautions

Avoid storing in extreme heat or freezing temperatures. Use only if temperature is above 45° F. Do not use in areas subject to constant moisture or as a waterproofing additive.

SPECTRUM BONDING AGENT and ACRYLIC ADMIXTURE is a professional strength re-emulsifiable concrete adhesive that bonds old concrete and new concrete, stucco, plaster, and mortar for stronger, more reliable repairs. **SPECTRUM BONDING AGENT and ACRYLIC ADMIXTURE** is easy to use and can be used on interior and exterior surfaces.

SURFACE PREPARATION

Surface must be structurally sound. Clean the surface of all loose materials and contaminants, including dust, dirt, oil, grease, sealers, and any other bond inhibitors.

MIXING AND APPLICATION GUIDE:

ADMIXTURE

With SPECTRUM Scratch & Brown Coat, Gray Finish Coat or SPECTRUM Mortars:

Premix dry, 1 part SPECTRUM CEMENT product with 2 to 3 parts sand. Dilute 1 part SPECTRUM BONDING AGENT and ACRYLIC ADMIXTURE with 3 to 4 parts water. Add the liquid to the dry sand/cement mix as needed to reach the desired consistency.

TOPPING or SHALLOW PATCH MIX

Premix dry, 1 part Portland Cement to 3 parts sand, or use suitable ready mix concrete. Dilute 1 part SPECTRUM BONDING AGENT and ACRYLIC ADMIXTURE with 1 to 2 parts water. Add the liquid to the sand/cement mix as needed to reach a trowelable consistency.

BONDING SLURRY

Mix 1 part Portland cement to 1 part sand and add SPECTRUM BONDING AGENT and ACRYLIC ADMIXTURE as needed to make a slurry. Then use a stiff bristle brush to apply the bonding slurry in a layer that is no more than 1/8 inch thick. Next apply the conventional coating of your choice (concrete, stucco, mortar) while the bonding grout is still soft and plastic.

BONDING AGENT

Apply undiluted SPECTRUM BONDING AGENT and ACRYLIC ADMIXTURE to an existing concrete surface and allow to become tacky. Weather and outside temperature will affect the drying time. **DO NOT ALLOW THE BONDER TO DRY COMPLETELY BEFORE PLACING CONCRETE, STUCCO or MORTAR.** If the bonder dries before you can place the concrete, re-prime the surface.

SHAKE WELL • KEEP FROM FREEZING

FIRST AID MEASURES:

Eye contact: Immediately flush the eye with cold water for 15 minutes and consult a physician.

Skin contact: Immediately wash with soap and water. If irritation persists, obtain medical advice.

Ingestion: Immediately call a physician and the nearest Poison Control Center.

REVIEW MATERIAL SAFETY DATA SHEET BEFORE USING THIS PRODUCT.

! CAUTION - KEEP OUT OF REACH OF CHILDREN !

AVOID EYE CONTACT & DO NOT TAKE INTERNALLY
24 HOUR EMERGENCY PHONE 1-800-424-9300

READ ALL SAFETY INFORMATION BEFORE APPLYING THIS PRODUCT!