



# EPS MASTIC



**Description:** EPS Mastic is a ready-mixed, ready to use acrylic based copolymer adhesive.

**Uses:** EPS Mastic is used to attach insulation board to prepared concrete, masonry or unpainted plywood surfaces. EPS Mastic should be used as an adhesive only. Not to be used as a base coat.

**Coverage:** 350 – 385 ft. per 5 gallon pail

**Dry Time:** Dry time will depend on the air temperature, humidity and porosity of the sheathing. Under normal conditions EPS Mastic will set within 24 hours and achieves full cure in seven days. Allow additional dry time during cold or humid days.

**Job Conditions:** Air and substrate temperatures must be 45° F or higher and must remain so for a minimum of 48 hours.

**Precautions:** Use adequate ventilation. Safety glasses and gloves should be worn. Keep out of reach of children. Harmful if swallowed. Dispose of in accordance with local, state or federal laws.

**Surface Preparation:** Surfaces to be coated should not be below 45° F and must be clean, dry and free of damage and all bond-inhibiting materials, including dirt, efflorescence, oils and other foreign matter. Loose, peeling, flaking or damaged pre-existing material should be removed by using a wire brush, water or sand blasting prior to application of EPS Mastic. Application over irregular surfaces should be avoided. Do not use on pressure treated wood or fire retardant treated surfaces. Do not use on damp surfaces or on substrates with high moisture content.

**Mixing:** Thoroughly mix EPS Mastic to a smooth, homogeneous consistency before application.

**Application:** Apply with a plastic or stainless notched trowel to the back of the insulation board. Immediately apply the insulation board to the wall with firm pressure to the entire surface. Insulation joints should not align with sheathing joints. Once applied, the working time is 15 minutes depending upon material, surface conditions and temperature.

**Clean Up:** Clean tools and equipment with water immediately after use.

**Storage & Shelf Life:** Store off the ground in a dry area. Protect from extreme heat, moisture, direct sunlight and freezing temperatures. Product can be stored for a period of 12 months in original un-opened container and protected from moisture. After opening, EPS Mastic will keep for several weeks if stored and resealed properly.

**Weight & Packaging:** Packaged in 5 gallon pails. 36 per pallet.

Houston  
2800 N. Gordon St.  
Alvin, TX 77511  
Ph: (281) 331-0088  
Fax: (281) 331-9813  
(800) 873-5794

Austin  
1585 Jack C. Hays Trail  
Buda, TX 78610  
Ph: (512) 312-0879  
Fax: (512) 295-3277  
(800) 499-0984

Dallas  
400 N Hwy 377  
Roanoke, TX 76262  
Ph: (817) 491-0531  
Fax: (817) 430-4370  
(800) 525-5382