

AHI Supply, LP
P.O. Box 884
Friendswood, Texas 77546
(800)873-5794, (281)331-0088 (281)331-9813 fax.
www.ahi-supply.com

To: **Date:**
Attention:
From:
Subject: The following material that we are submitting for your approval on behalf of.
Project:

EPS Mastic

Product information

EPS is a ready-mixed, ready to use acrylic based copolymer adhesive. It is formulated to adhere to architectural expanded polystyrene (EPS) foam shapes. It is also used as an adhesive for wood-based sheathing. EPS Mastic comes with a 5 year limited material warranty.

Features

Water-based	Ready to Use	Neutral White
Interior or Exterior	Notched Trowel Application	

General information

EPS Mastic should be used as an adhesive only. Please note do not use as a base coat, on pressure treated lumber or fire retardant surfaces. Thoroughly mix EPS Mastic to a smooth, homogeneous consistency before application. After mixing the working time of the adhesive is approximately 1 to 3 hours (once applied the working time on individual forms is approximately 15 minutes). Clean area and remove all dust grease, oil, paint, dirt, efflorescence and any unsound concrete. Use a plastic or stainless steel notched trowel for application. Do not allow the surface of the EPS Mastic to form a skin before positioning foam shapes. When used to bond EPS board or EPS shapes to an approved substrate, allow 24 hours to dry before working on the next phase of stucco application. Please note that you should not apply EPS Mastic when the temperature outside is lower than 40 degrees Fahrenheit or when frost is predicted. Do not use in wet areas and protect work from rain for at least 24 hours.

Coverage on textures

All coverages are approximate, dependent on substrate and individual application techniques.
350 sq. ft.- 385 sq. ft.

Thank you for the opportunity of furnishing this quality product on your important project! We look forward to working with you all!