

AHI Supply, LP
P.O. Box 884
Friendswood, Texas 77546
(800)873-5794, (281)331-0088 (281)331-9813 fax.
www.ahi-supply.com

To: _____ **Date:** _____
Attention: _____
From: _____
Subject: The following material that we are submitting for your approval on behalf of.
Project: _____

Spectrum Acrylic Stucco Finishes

Product information

Spectrum Acrylic Stucco Finishes are acrylic-based products that are weather resistant wall coatings. Users often prefer this product due to its smooth, creamy texture along with the purity and whiteness of the aggregates that it contains. Some of our competitors use less expensive and darker silica based aggregates in their finish. Spectrum Acrylic Stucco Finish will be more attractive on the wall than those competitive products that contain the lower quality ingredients. This product is available in 30 standard colors and 6 decorative textures. AHI also has the ability to make Custom tints to match existing stucco color inspirations by our trained experts. Spectrum Acrylic Stucco Finish coats come with a 5 year limited material warranty.

Features

Decorative Colors	Mildew Resistant	Alkali Resistant
Interior or Exterior	Trowel or Spray Apply	Water/Crack Resistant

General information

Spectrum Acrylic Stucco Finishes are used as decorative coatings over conventional stucco application standards. Other widely used applications are any cementitious surface (stucco, block, poured concrete and masonry surfaces). Clean area and remove all dust, grease, oil, paint, dirt, efflorescence and any unsound concrete. We recommend Spectrum Fiber Reinforced Scratch and Brown Coat to adhere to lath surface. Please note that Spectrum Acrylic Primer must be applied over uncured cementitious materials to ensure that improper pH levels do not cause stucco coating failures or shadowing issues. Please note that you should not apply stucco coating when the temperature outside is lower than 40 degrees Fahrenheit or when frost is predicted. Thoroughly mix product to a smooth, homogeneous consistency before application. Do not use in wet areas and protect work from rain for a least 24 hours.

Coverage on textures

All coverages are approximate, dependent on substrate and individual application techniques.

Smoothest	to	Coarse
Adobe 90 sq.ft.-120 sq ft.		Marble Blast 95 sq. ft. - 125 sq. ft
Sand 100 sq. ft.-130 sq. ft.		Medium 90 sq. ft -120 sq. ft.
Swirl 90 sq. ft.-120 sq. ft.		Rough 80 sq. ft.-110 sq

Thank you for the opportunity of furnishing this quality product on your important project! We look forward to working with you all!