



Spectrum Elastomeric Finish

Description: Spectrum Elastomeric Finish is a 100% elastomeric-based product that is a weather resistant wall coating available in six textures and 40 standard colors, along with custom color matching.

Uses: Used as an interior or exterior decorative coating over wood, stucco or any cementitious surface such as block, poured concrete and masonry surfaces.

Coverage: Coverage varies depending on finish selected. Adobe Finish: 90 – 120 sq. ft.; Sand Finish: 100 – 130 sq. ft.; Medium Finish: 90 – 120 sq. ft.; Swirl Finish: 90 -120 sq. ft.; Rough Finish: 80 – 110 sq. ft.; Marble Blast: 90-130 sq. ft.

Dry Time: Coatings will dry to the touch in 3 to 4 hours at 70° F. Protect coatings from rainfall for at least 24 hours after application.

Job Conditions: Air and substrate surface temperature must be 40°F or higher and remain so for a minimum of 24 hours.

Precautions: Use adequate ventilation. Keep away from small children. Harmful if swallowed. Contact physician or poison control office immediately if ingested. Dispose of in accordance with local, state and federal laws.

Surface Preparation: Clean area and remove all dust, grease, oil, paint, dirt, efflorescence and any unsound concrete. Please note: Spectrum Acrylic Primer must be applied over uncured cementitious materials to ensure that improper pH levels do not cause coating failures or shadowing issues. Elastomeric finishes and paints are applied when the cementitious material has cured to a proper pH level of 10 or below and the primer has dried for quick dry time of 30 minutes.

Light Reflectivity: Spectrum Coatings use high quality pigments to tint the finish coatings. Ultra-violet and sunshine exposure can and will cause fading issues over time. To help minimize fading, light colors should be selected. Light reflectance values are rated 100% white - 0% black. The higher the lightness value, the less fading occurs. Dark colors (light reflectivity less than 20) will fade more rapidly than light colors.

Mixing: Mix for 5 minutes with paddle mixer.

Application: Apply with stainless steel trowel to a thickness of the largest aggregate. If using a plastic trowel, float the finish in a figure eight motion, only stopping at natural breaks such as corners, expansion joints etc.

Clean Up: Clean tools and equipment with water immediately after use.

Storage & Shelf Life: Store off the ground in a dry area. Protect from extreme heat, moisture, direct sunlight and freezing temperatures. Product can be stored for a period of 12 months in original un-opened container and protected from moisture. After opening, Spectrum Elastomeric Finish will keep for several weeks if stored and resealed properly.

Weight & Packaging: Weights vary due to pigment content. Packaged in 5 gallon containers. 36 containers per pallet.

Warranty: All Spectrum Stucco products come with a limited 5 year warranty.

Houston
2800 N. Gordon St.
Alvin, TX 77511
Ph: (281) 331-0088
Fax: (281) 331-9813
(800) 873-5794

Austin
1585 Jack C. Hays Trail
Buda, TX 78610
Ph: (512) 312-0879
Fax: (512) 295-3277
(800) 499-0984

Dallas
400 N Hwy 377
Roanoke, TX 76262
Ph: (817) 491-0531
Fax: (817) 430-4370
(800) 525-5382