

AHI Supply, LP
P.O. Box 884
Friendswood, Texas 77546
(800)873-5794, (281)331-0088 (281)331-9813 fax.
www.ahi-supply.com

To:

Date:

Attention:

From:

Subject: The following material that we are submitting for your approval on behalf of.

Project:

Spectrum Elastomeric Stucco Finishes

Product information

Spectrum Elastomeric Stucco Finishes have an elastomeric binder to bridge hairline cracks and are also weather resistant wall coatings. Elastomeric is recommended mostly in areas where the coating needs to be better protected from heavy wind and rain as it has a firmer consistence. Users often prefer this product due to its smooth, creamy texture along with the purity and whiteness of the aggregates that it contains. Some of our competitors use less expensive and darker silica aggregates in their finish. Spectrum Elastomeric Stucco Finish will be more attractive on the wall than those competitive products that contain the lower quality ingredients. This product is available in 30 standard colors and 6 decorative textures. AHI also has the ability to make Custom tints to match existing stucco color inspirations by our trained experts. Spectrum Elastomeric Stucco Finish coats come with a 5 year limited material warranty.

Features

Decorative Colors	Alkali Resistant	Trowel or Spray Apply
Interior or Exterior	Water/Crack Resistant	

General information

Spectrum Elastomeric Stucco Finishes are used as decorative coatings over conventional stucco application standards. Other widely used applications are any cementious surface, (stucco, block, poured concrete and masonry surfaces). Clean area and remove all dust, grease, oil, paint, dirt, efflorescence, and any unsound concrete. We recommend Spectrum Fiber Reinforced Scratch and Brown Coat to adhere to lath surface. Please note that Spectrum Acrylic Primer must be applied over uncured cementious materials to ensure that improper pH levels do not cause stucco coating failures or shadowing issues. Please note that you should not apply stucco coating when the temperature outside is lower than 40 degrees Fahrenheit or when frost is predicted. Thoroughly mix product to a smooth, homogeneous consistency before application. Do not use in wet areas and protect work from rain for at least 24 hours.

Coverage on textures

All coverages are approximate, dependent on substrate and individual application techniques.

Smoothest	To	Coarse
Adobe 90 sq.ft.-120 sq ft.		Marble Blast 95 sq. ft. - 125 sq. ft
Sand 100 sq. ft.-130 sq. ft.		Medium 90 sq. ft -120 sq. ft.
Swirl 90 sq. ft.-120 sq. ft.		Rough 80 sq. ft.-110 sq.

Thank you for the opportunity of furnishing this quality product on your important project! We look forward to working with you all!