



Spectrum Paint (Acrylic)

Description: Spectrum Acrylic Paint is used as a weather resistant wall coating that is available in 30 standard colors. Custom tinting is also available.

Uses: Used as an interior or exterior decorative coating over wood, stucco or any cementitious surface such as stucco, block, poured concrete and masonry surfaces.

Coverage: Spectrum Acrylic Paint will cover 1500-1800 sq. ft at 4 mils thick wet application. Certain colors may require two coats for complete hide. Coverage also depends on surface texture, porosity and application method.

Dry Time: Allow 2 hours touch, 4 hours recoat. Actual dry time will depend on surface temperatures, humidity and porosity of material being painted.

Job Conditions: Air and substrate surface temperature must be 40°F or higher and remain so for a minimum of 24 hours. Also protect work from rain for at least 24 hours.

Precautions: Use adequate ventilation. Keep away from small children. Harmful if swallowed. Contact physician or poison control office if ingested. Dispose of in accordance with local, state and federal laws.

Surface Preparation: Clean area and remove all dust, grease, oil, paint, dirt, efflorescence and any unsound concrete. Please note: **Spectrum Acrylic Primer** must be used to ensure that improper pH levels do not cause paint coating failures or shadowing issues. This will also help prevent water from penetrating beneath the finish and cause peeling.

Light Reflectivity: Spectrum Coatings use high quality pigments to tint the finish coatings. Ultra-violet and sunshine exposure can and will cause fading issues over time. To help minimize fading, light colors should be selected. Light reflectance values are rated 100% white - 0% black. The higher the lightness value, the less fading occurs. Dark colors (light reflectivity less than 20) will fade more rapidly than light colors.

Mixing: Mix for 5 minutes before application with paint stirrer.

Application: Apply with brush, roller or sprayer to desired coverage or thickness.

Clean Up: Clean tools and equipment with water immediately after use.

Storage & Shelf Life: Store off the ground in a dry area. Protect from extreme heat, moisture, direct sunlight and freezing temperatures. Product can be stored for a period of 12 months in original un-opened container and protected from moisture. After opening, Spectrum Paint will keep for several weeks if stored and resealed properly.

Packaging: Packaged in 5 gallon containers. 36 containers per pallet.

Houston
2800 N. Gordon St.
Alvin, TX 77511
Ph: (281) 331-0088
Fax: (281) 331-9813
(800) 873-5794

Austin
1585 Jack C. Hays Trail
Buda, TX 78610
Ph: (512) 312-0879
Fax: (512) 295-3277
(800) 499-0984

Dallas
400 N Hwy 377
Roanoke, TX 76262
Ph: (817) 491-0531
Fax: (817) 430-4370
(800) 525-5382