



# COLOR SELECTION GUIDE

Spectrum Acrylic and Elastomeric Coatings are recommended as low-maintenance, weather-resistant, exterior wall coatings. Spectrum stucco coatings are available in 30 standard colors and 6 different textures, as well as paint and primer. Spectrum also offers custom color matching performed by our factory trained technicians. All textures and colors are available in an acrylic or elastomeric base giving Spectrum coatings the ability to be applied to almost any cementitious surface (stucco, block, poured concrete, and masonry surfaces).

## Traditional Application



Textures are shown left to right from finest (containing the smallest aggregate) to coarsest (containing the largest aggregate).



**Houston Corporate Office**  
 2800 North Gordon  
 Alvin, TX 77511  
 (800) 873-5794  
 (281) 331-0088

**Dallas-Fort Worth**  
 400 N Hwy 377  
 Roanoke, TX 76262  
 (800) 525-5382  
 (817) 491-0531

**Austin-Buda**  
 1585 Jack C Hays Trail  
 Buda, TX 78610  
 (800) 499-0984  
 (512) 312-0879

[www.ahi-supply.com](http://www.ahi-supply.com)



**04 - China White**



**10 - Vandyke**



**11 - Tumbleweed**



**13 - Golden Tan**



**14 - Wheat Straw**



**16 - Canvas Tan**



**17 - Desert Tan**



**18 - Driftwood**



**19 - European Gray**



**20 - Stonewall**



**23 - Bleached Sand**



**25 - Plantation Beige**



**26 - Bone White**



**27 - Desert Fawn**



**29 - Sienna Sand**



**30 - Clay Beige**



**31 - Chalk Beige**



**34 - Harvest Tan**



**35 - Frontier Tan**



**37 - Light Pewter**



**38 - Biscuit**



**39 - Country Gray**



**40 - Wet Sand**



**41 - Brown Sienna**



**42 - Victorian Suede**



**43 - Mocha Cream**



**44 - Oak Haze**



**45 - Colonial Beige**



**46 - Sandlewood Ash**



**47 - Southern Mesa**

AHI assumes no responsibility for any color discrepancies after customer has approved color samples and texture. Final color approval is the responsibility of the customer and samples can be made as needed. Variations in color may be expected due to stucco texture choice, job conditions, method of application and slight variations of natural raw materials. For best color consistency, use finish with the same batch number within a wall section. Color variations can and should be expected if all finish is not ordered at the same time. For excellent results, please read and follow all mixing, application, and safety information found on the product literature and labels. Please note: Spectrum Acrylic Primer must be applied over uncured cementitious materials to ensure that improper pH levels do not cause coating failures or shadowing issues.